

Data Sheet

Savvio® 10K.5

The Optimal Balance of Capacity, Performance and Power in a 10K, 2.5-Inch Enterprise Drive

Key Advantages

- Improves storage efficiency with 50% increase in capacity and 18% increase in sustained data rate performance over previous generation
- Delivers the highest-capacity 2.5-inch, 10K-RPM hard drive (up to 900GB) to manage more data without increasing the number of drives
- First SFF drive platform to offer four capacity points on a single platform
- PowerChoice™ technology for T10-compliant power management enables systems tailored for performance and power consumption
- Reduces system design, qualification and inventory costs for OEMs
- Protection Information (PI) protects against inadvertent data change.¹
- Self-Encrypting Drive (SED) option (AES-256) cuts IT drive retirement costs while securely protecting data where it lives—on the drive.²
- FIPS 140-2 Validated™ drives protect *Sensitive but Unclassified* and *Protected* class data.^{2,3}
- Seagate Unified Storage architecture reduces complexity and costs.

Best-Fit Applications

- Mission-critical servers and external storage arrays
- Power- and space-constrained data centers
- Compliance or data security initiatives

¹ Protection Information (PI) feature requires PI-compliant host or controller support.

² Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

³ See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>



Savvio® 10K.5



The Optimal Balance of Capacity, Performance and Power in a 10K, 2.5-Inch Enterprise Drive

Improves Storage Efficiency

The Savvio® 10K.5 drive is the highest-capacity 2.5-inch, 10K drive and the first SFF drive to offer four capacity points on a single platform. This drive enables improved storage efficiency by providing up to 900GB in a single drive, helping data centers manage more data without increasing the number of drives, all while increasing sustained data rates by 18% (over previous generation) and maintaining favorable power consumption rates. The small form factor allows enterprises to solve space constraints through higher-density storage.

Seagate PowerChoice™ technology enables OEMs and data centers to tailor systems for performance and power consumption, enabling green IT initiatives.

Reduces Costs and Complexity

The Savvio 10K.5 drive reduces system complexity by standardizing on a common form factor, storage interface and encryption technology. This means fewer device types, form factors, interfaces and security technologies need to be deployed, inventoried and managed.

Enables Smoother Transitions

OEMs and data centers have the flexibility to maintain or upgrade capacity, transition from 3.5- to 2.5-inch form factors, and/or migrate from Fibre Channel to SAS drives in one or more steps. With four capacity points on the same drive platform, the Savvio 10K.5 drive enables easier support for current systems and optimized return on existing investments.

Protects Data

Protection Information and Self-Encrypting Drive options protect data from corruption during the storage process and from exposure should the device be lost, stolen, or retired—helping organizations meet compliance and data security objectives. Seagate Instant Secure Erase makes drive retirement and repurposing safe, fast and affordable.

| Specifications | 900GB ¹ | 600GB ¹ | 450GB ¹ | 300GB ¹ |
|--|----------------------------|----------------------------|----------------------------|----------------------------|
| SAS Model Number | ST9900805SS | ST9600205SS | ST9450405SS | ST9300605SS |
| SED Model Number | ST9900705SS ² | ST9600105SS ² | ST9450305SS ² | ST9300505SS ² |
| SED FIPS 140-2 SAS Model Number | ST9900605SS ^{2,3} | ST9600005SS ^{2,3} | ST9450205SS ^{2,3} | ST9300405SS ^{2,3} |
| FC Model Number | ST9900805FC | ST9600205FC | ST9450405FC | ST9300605FC |
| Capacity | | | | |
| Formatted 512 Bytes/Sector (GB) | 900 | 600 | 450 | 300 |
| External Transfer Rate (MB/s) | | | | |
| 6Gb/s Serial Attached SCSI | 600 | 600 | 600 | 600 |
| 4Gb/s Fibre Channel | 400 | 400 | 400 | 400 |
| Performance | | | | |
| Spindle Speed (RPM) | 10K | 10K | 10K | 10K |
| Average Latency (ms) | 3.0 | 3.0 | 3.0 | 3.0 |
| Seek Time | | | | |
| Average Read/Write (ms) | 3.7/4.1 | 3.4/3.8 | 3.4/3.8 | 3.4/3.8 |
| Track-to-Track Read/Write (ms) | 0.2/0.4 | 0.2/0.4 | 0.2/0.4 | 0.2/0.4 |
| Sustained Transfer Rate | | | | |
| Outer to Inner Diameter (MB/s) | 168 to 93 | 168 to 93 | 168 to 93 | 168 to 93 |
| Cache, Multisegmented (MB) | 64 | 64 | 64 | 64 |
| Configuration/Reliability | | | | |
| Disks | 3 | 2 | 2 | 1 |
| Heads | 6 | 4 | 3 | 2 |
| Nonrecoverable Read Errors per Bits Read | 1 per 10E16 | 1 per 10E16 | 1 per 10E16 | 1 per 10E16 |
| Annualized Failure Rate (AFR) | 0.44% | 0.44% | 0.44% | 0.44% |
| Power Management | | | | |
| Typical Op (A), Random Read +5V/+12V | 0.46/0.48 | 0.46/0.45 | 0.48/0.46 | 0.46/0.43 |
| Power Idle (W) | 4.4 | 3.8 | 3.8 | 3.5 |
| Environmental | | | | |
| Temperature, Operating (°C) | 5 to 55 | 5 to 55 | 5 to 55 | 5 to 55 |
| Temperature, Nonoperating (°C) | -40 to 70 | -40 to 70 | -40 to 70 | -40 to 70 |
| Shock, Operating: 11ms (Gs) | 40 | 40 | 40 | 40 |
| Shock, Nonoperating: 2ms (Gs) | 400 | 400 | 400 | 400 |
| Acoustics Idle (bels—sound power) | 3.0 | 3.0 | 3.0 | 3.0 |
| Vibration, Operating: <500Hz (Gs) | 0.5 | 0.5 | 0.5 | 0.5 |
| Vibration, Nonoperating: <500Hz (Gs) | 3.0 | 3.0 | 3.0 | 3.0 |
| Physical | | | | |
| Height (in/mm, max) ⁴ | 0.591/15.00 | 0.591/15.00 | 0.591/15.00 | 0.591/15.00 |
| Width (in/mm, max) ⁴ | 2.760/70.10 | 2.760/70.10 | 2.760/70.10 | 2.760/70.10 |
| Depth (in/mm, max) ⁴ | 3.955/100.45 | 3.955/100.45 | 3.955/100.45 | 3.955/100.45 |
| Weight (lb/kg) | 0.451/0.205 | 0.475/0.215 | 0.477/0.216 | 0.465/0.211 |
| Carton Unit Quantity | 30 | 30 | 30 | 30 |
| Cartons per Pallet | 50 | 50 | 50 | 50 |
| Cartons per Layer | 10 | 10 | 10 | 10 |
| Warranty | | | | |
| Limited Warranty (years) | 5 | 5 | 5 | 5 |

www.seagate.com



AMERICAS
ASIA/PACIFIC
EUROPE, MIDDLE EAST AND AFRICA

Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000
Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2012 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerChoice, Savvio, Seagate Secure and the Unified Storage architecture logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The FIPS logo is a certification mark of NIST, which does not imply product endorsement by NIST, the U.S., or Canadian governments. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications. DS127.4-1201US, January 2012

1 One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.
2 Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.
3 See FIPS 140-2 Level 2 Certificate at <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>
4 These base deck dimensions conform to the Small Form Factor Standard (SFF-8201) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.